



Technical Product Description

JAC Brilliant Gloss / WLK202 / B90 P

Sheet Size: 700*1000

Product Code: 1119

Issue date: 12-Feb-2004

Print Carrier

Brilliant Gloss

Brilliant Gloss is a white high gloss cast coated paper which is suitable for high quality printing by a number of processes and provides an excellent base for a range of embellishment techniques, such as embossing and foil stamping. The use of overvarnish is essential to enhance surface water repellency when used for labels exposed to moisture from condensation during filling/labelling, storage or refrigeration. Application include a range of prestige labels on premium products, as well as general product and point of sale label.

Typical Physical Properties

Weight	80 g/m ²
Thickness	85 µm

Adhesive

WLK202

WLK202 is a strong acrylic adhesive with extremely high tack and good adhesion for application to wine, champagne and other beverage bottles. Tested and proven on surfaces affected by condensation, dry and recycled bottles, labels do not slip or move on bottles after application. Although WLK202 exhibits excellent water resistance for optimum performance it is recommended that labels be UV varnished. WLK202 is an ideal adhesive to use for neck labels but it is recommended however, that where such labels are embossed or applied over the cap, trials should be conducted to determine suitability.

Typical Physical Properties

Adhesion	FTM1	600 N/m
Tack°	FTM9	360 N/m
Min. Application Temp	5 °C --> +40 °C	
Service Temp	-30 °C --> +70 °C	

Release Liner

B90

A high strength woodfree kraft paper with good dimensional stability and flatness during processing, combined with the resilience required for high speed die cutting operations.

Typical Physical Properties

Weight	87 g/m ²
Thickness	92 µm

Solid

Good dimensional stability and flatness during processing.

Shelf Life

Two years, stored at 22°C / 50% RH



Avery Dennison Materials Pty Ltd
95 Sunshine Road
Tottenham VIC 3012
Australia
Tel +61 3 8325 8300
Fax +61 3 8325 8388

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free from defects in the material or workmanship for a period of one year from date of shipment. Any products shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge or AVERY DENNISON may issue a credit in such an amount as it deems reasonable

however, in no way shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO THE PRODUCTS DESCRIBED HEREIN. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN AUTHORIZED REPRESENTATIVE OF AVERY DENNISON.

No salesperson, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.